


## LED DRIVER 10-45VDC 250-1000MA 32W 129,5X97X30MM

€ 22,95

Excl. BTW: € 18,97

### Afbeeldingen



Param.	Value	Unit	Min.	Max.	Temp.	Notes
Input Voltage	10-45	VDC				
Output Voltage	24	VDC				
Output Current	250-1000	mA				
Power	32	W				
Efficiency	85	%				
Power Factor	0.95					
THD	15	%				
Surge Current	1000	mA				
Surge Power	64	W				
Operating Temp.	-25 to +70	°C				
Storage Temp.	-40 to +100	°C				
Humidity	5 to 95	%				
Shock	10	g				
Vibration	10	g				

### Beschrijving

#### Features

- Multipower driver supplied with dip-switch for the selection of the output current.
- IP20 independent driver, for indoor use (PROFESSIONALE 42).
- Class II protection against electric shock for direct or indirect contact (PROFESSIONALE 42).
- Driver for built-in use (PROFESSIONALE 42 BI).
- It can be used for lighting equipment in protection class I and II (PROFESSIONALE 42 BI).
- Active Power Factor Corrector.
- Current regulation  $\pm 5\%$  including temperature variations.
- Input and output terminal blocks on opposite sides (wire cross-section up to 1,5 mm<sup>2</sup> / AWG15).
- Clamping screws on primary and secondary circuits for cables with diameter: min. 2 mm - max. 11 mm (PROFESSIONALE 42).
- Driver can be secured with slot for screws.
- Protections:
  - against overheating and short circuits;
  - against mains voltage spikes;
  - against overloads.
- Thermal protection = C.5.a.

[Klik hier om de datasheet te bekijken](#)

## Productinformatie

---

Artikelnummer	127484N
Merk	TCI
Is on Sale	Nee

