

VOEDING 24V 2500MA GESCHAKELD

€ 32,95

Excl. BTW: € 27,23

Afbeeldingen



Beschrijving

Features

- Plug-in switching power supply with europlug
- Universal input
- LPS
- Protections: short circuit/over load/over voltage
- Protection class II
- Very low no load power consumption
- Energy level: (EU) 2019/1782+ Level VI
- Safety standards: EN62368-1; IEC62368-1
- 3 years manufacturer warranty



Technical Specifications



Input Voltage:	90...264V AC (47...63Hz)
	127...370V DC
Input Inrush Current, Max.:	50A
No Load Power Consumption, Max.:	<0,15W
Operating Temperature:	-20...+70°C
Cable Length	
5...15V:	100cm
24V:	150cm
Input Plug:	Eurostecker
Output Plug:	5,5x2,1mm Hohlstecker
Average active efficiency	
for 5V:	86,2%
for 12/15/24/48V:	89,02%
Efficiency at low load, typ. (10%):	84,59%
Weight:	208g



Part Nr.	U_A	I_A	P_A	ΔU_A	U_{RN}	η
	[V]	[A]	[W]	[%]	[mV _{p-p}]	[%]
PSS2424	24	0...2,5	60	2	100	89

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, ΔU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, η = Efficiency

Productinformatie

Artikelnummer	PSS2424
Merk	MEANWELL
Is on Sale	Nee

