


## GESCHAKELDE VOEDING SINGLE OUTPUT 1500W 15V/100A

€ 499,00

Excl. BTW: € 412,40

### Afbeeldingen



### Beschrijving

#### Features

- Enclosed case, built-in fan, screw terminals
- Universal input
- Overload protection, current limiting, hiccup after 5s
- Protections: short circuit/over load/over voltage
- Built-in active PFC function
- Low profile
- Parallel function
- Active current sharing up to 6000W (3+1 units)
- Built-in remote On/Off control
- Power fail signal
- Built-in remote sense function
- Built-in auxiliary power 12V/0,1A
- EMC: Conducted Emission EN55032/EN55011 Class B, Radiated Emission EN55032/EN55011 Class A



## Technical Specifications



Input Voltage:	90...264V AC (47...63Hz)
	127...370V DC
Input Inrush Current, Max.:	60A
Leakage Current, Max.:	2mA
Output Voltage Adjustment:	±10%
Over Load Protection:	105...135%
Withstand Voltage	
I/P-O/P:	3000V AC
I/P-FG:	2000V AC
O/P-FG:	500V AC
Operating Temperature:	-20...+70°C
Weight:	3000g

I/P = Input, O/P = Output, FG = Frame Ground



Part Nr.	$U_A$	$I_A$	$P_A$	$DU_A$	$U_{RN}$	h
	[V]	[A]	[W]	[%]	[mV <sub>p-p</sub> ]	[%]
RSP-1500-5	5	0...240	1200	2	150	80
RSP-1500-12	12	0...125	1500	1	150	87
RSP-1500-15	15	0...100	1500	1	150	87
RSP-1500-24	24	0...63	1512	1	150	90
RSP-1500-27	27	0...56	1512	1	150	90
RSP-1500-48	48	0...32	1536	1	200	91

$U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise, h = Efficiency

## Productinformatie

---

Artikelnummer	RSP150015
Merk	MEANWELL
Is on Sale	Nee

