


ELCO BUS 22000UF 100V SCHROEFAANSLUITING

€ 69,95

Excl. BTW: € 57,81

Afbeeldingen



Beschrijving

Technical Specifications

| Part Nr. | C | U _N | tand | I _R | Z |
|----------|--------|----------------|------|----------------|--------|
| | [μF] | [V DC] | [%] | [A] | [mOhm] |
| EBG33A | 33000 | 40 | 25 | 8,7 | 10 |
| EBG15A | 150000 | 40 | 47 | 16,5 | 8 |
| EBF33A | 330000 | 40 | 62 | 35,2 | 3 |
| EBG75A | 750000 | 40 | 93 | 55,3 | 2 |

| | | | | | |
|---------|-------|-----|----|------|----|
| EBF10CA | 10000 | 100 | 10 | 9,4 | 16 |
| EBF22C | 22000 | 100 | 9 | 15 | 7 |
| EBF47C | 47000 | 100 | 12 | 28,2 | 4 |
| EBE15D | 1500 | 400 | 7 | 3,8 | 74 |
| EBE33D | 3300 | 400 | 8 | 5,8 | 39 |
| EBE68D | 6800 | 400 | 8 | 12,4 | 17 |
| EBF12D | 12000 | 400 | 8 | 14,8 | 8 |

C = Rated Capacitance, Rated Voltage DC, tan d = Dissipation Factor Max. (20°C) , I_R = Ripple Current (100Hz, 85°C), Z = Impedance (20°C, 10kHz)



Dimensions

| Part Nr. | D | L | a | h | B | Terminals |
|----------|------|------|------|------|--------|-----------|
| | [mm] | [mm] | [mm] | [mm] | | |
| EBG33A | 50 | 70 | 22 | 5 | M12x16 | M5 |
| EBG15A | 75 | 145 | 31,7 | 5 | M12x16 | M5 |
| EBF33A | 75 | 165 | 31,7 | 5 | M12x16 | M5 |
| EBG75A | 90 | 230 | 31,7 | 5 | M12x16 | M6 |
| EBF10CA | 40 | 70 | 18 | 5 | M8x12 | M5 |
| EBF22C | 65 | 100 | 28,5 | 5 | M12x16 | M5 |
| EBF47C | 75 | 145 | 31,7 | 5 | M12x16 | M5 |
| EBE15D | 50 | 100 | 22 | 5 | M12x16 | M5 |
| EBE33D | 75 | 100 | 31,7 | 5 | M12x16 | M5 |
| EBE68D | 75 | 145 | 31,7 | 5 | M12x16 | M5 |
| EBF12D | 90 | 160 | 31,7 | 5 | M12x16 | M6 |



Norms

IEC 60384-4, climatic category 40/O85/56

Productinformatie

| | |
|---------------|--------|
| Artikelnummer | EBF22C |
| Merk | F&T |
| Is on Sale | Nee |

