


DIN-RAIL VOEDING 105MM 150W 24V/6,25A

€ 47,95

Excl. BTW: € 39,63

Afbeeldingen



Beschrijving

Features

- Direct assembly on DIN Rail
- Enclosed case, Touch-guard screw terminals
- Universal input
- Overload protection, current limiting, auto recovery
- Protections: short circuit, over load, over voltage
- Low no load power consumption
- Power-on LED display
- Insulation Class II



Technical Specifications



Input Voltage:

85...264V AC (47...63Hz)

120...370V DC

Input Inrush Current, Max.:	70A
Over Load Protection:	105...135%
Withstand Voltage, I/P-O/P:	4000V AC
Operating Temperature:	-30...+70°C
Weight:	310g

I/P = Input, O/P = Output



Part Nr.	U_A	I_A	P_A	DU_A	U_{RN}	h
	[V]	[A]	[W]	[%]	[mV _{p-p}]	[%]
HDR10012	12	11,3	135,6	2	120	89
HDR10015	15	9,5	142,5	1	120	89,5
HDR10024	24	6,25	150	1	150	90,5
HDR1048	48	3,2	153,6	1	240	90,5

U_A = Output Voltage, I_A = Output Current, P_A = Output Power, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Productinformatie

Artikelnummer	HDR15024
Merk	MEANWELL
Is on Sale	Nee

