

DIN-RAIL VOEDING 32MM 75W 12V/6,3A

€ 34,94

Excl. BTW: € 28,88

Afbeeldingen



Beschrijving

Features

- Direct assembly on DIN Rail
- Enclosed case, Touch-guard screw terminals
- Universal input
- Overload protection, current limiting, auto recovery
- Protections: short circuit/over load/over voltage
- DC OK LED display



Technical Specifications



Input Voltage:

90...264V AC (47...63Hz)

127...370V DC

Input Inrush Current, Typ.:	35A
Leakage Current, Max.:	1mA
Output Voltage Adjustment:	+12%
Over Load Protection:	105...130%
Withstand Voltage	
I/P-O/P:	3000V AC
I/P-FG:	2000V AC
O/P-FG:	500V AC
Operating Temperature:	-20...+70°C
Weight:	510g

I/P = Input, O/P = Output, FG = Frame Ground



Part Nr.	U_A	I_A	P_A	DU_A	U_{RN}	h
	[V]	[A]	[W]	[%]	[mV _{p-p}]	[%]
NDR-75-12	12	0...6,3	75,6	2	80	85,5
NDR-75-24	24	0...3,2	76,8	1	120	88
NDR-75-48	48	0...1,6	76,8	1	150	89

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Productinformatie

Artikelnummer	NDR7512
Merk	MEANWELL
Is on Sale	Nee

