

DIN 5P FEMALE PLASTIC 360°

€ 1,52

Excl. BTW: € 1,26

Afbeeldingen



Beschrijving

DIN socket, straight version, shielded, with one-piece inner shell, bend protection and solder terminals

Grey version on request

1. Temperature range $-25 \text{ }^{\circ}\text{C}/+70 \text{ }^{\circ}\text{C}$

2. Materials

Body PA 6.6 GF, HB according to UL 94

Contact spring CuZn, undernickel and tinned

CuSn, silvered

Sleeve steel, undercoppered and nicked

Housing PE, HB according to UL 94

3. Mechanical data

Insertion force/contact \hat{A} 7 N

Withdrawal force/contact \hat{A} 1 N

Cable diameter 6.0 mm

Mating with DIN plugs S, XS

Connectable conductors solder terminal

max. section 0.34 mm²

4. Electrical data

Contact resistance \hat{A} 10 m Ω (earth contact \hat{A} 30 m Ω)

Rated current 4 A

Rated voltage 34 V AC

Test voltage 1 kV AC/60 s

Insulation resistance > 10 G Ω (XK 52, 72, 82 > 1 k Ω)

1 measured with a polished steel pin, nominal thickness 1.5 mm)

Productinformatie

Artikelnummer	DNK05PC
Merk	Merk
Is on Sale	Nee

