

HOORNSPEAKER 100V 15W 210X269MM

€ 129,00

Excl. BTW: € 106,61

Afbeeldingen



Beschrijving

Re-entrant horn speaker with 100 V transformer. Light grey plastic housing. Level adjustment for 100 V model via knob, in addition 20 Ohm possible. High sound pressure and wide range of frequency response guarantee excellent voice quality. Pivoting metal frame for mounting walls, ceilings, columns etc.

Typical applications:

- PA systems in factory halls, railway stations etc.
- outdoor PA

Attributes:

- functionally at low temperature according to EN 60068-2-1 (-40 °C; 96 h)
- up to the standards of the Germanischer Lloyd (requirements for electrical equipment / low temperature)
- Plastic: ABS (UL 94: HB)
- Metall frame: Stainless steel (1.4301)

Transformer matching 15; 10; 5; 3; 1 W; 20 Ohm

Sound pressure level 110 dB (1 W/1 m)

@ 2644 Hz

Frequency response 500- 5500 Hz

Mean sound pressure level 107 dB (1 W/1 m)

Max. sound pressure level 119 dB (15 W/1 m)

Opening angle (-6 dB) 37°/4000 Hz

Net weight 1,8 kg

Length of cable 0,6 m

Protective system IP 66

Temperature range -40 ... 80 °C
Colour hellgrau/light grey
ähnlich/similar RAL 7035

Productinformatie

Artikelnummer	DK8P/15W
Merk	VISATON
Is on Sale	Nee

