

EINDBUIS 8P OKTAL BEAM PENTODE

€ 105,00

Excl. BTW: € 86,78

Afbeeldingen



Beschrijving

A. F. BEAM PENTODE

Base: OCTAL

U_f = 6,3 V

I_f = cca 1,3 A

Typical characteristic:

U_a = 250 V

U_{g2} = 250 V

-U_{g1} = 15 V
I_a = 85 mA
I_{g2} = max. 7 mA
S = 6 mA/V
R_i 22,5 k_Ω,
Triode connected
U_{a,g2} = 250 V
-U_{g1} = 15 V
R_a = 1,3 k_Ω,

Limiting values:

U_a = 550 V
U_{g2} = 550 V
-U_{g1} = 200 V
W_a = 25 W
W_{g2} = 3,5 W
W_{a,g2} = 27 W
I_k = 150 mA
U_{k/f} = 200 V
R_{g1-k} (catode bias)
W_{a+g2} ≤ 27 W 1 M_Ω,
W_{a+g2} > 27 W 500 k_Ω,
R_{g1-k} (fixed bias)
W_{a-g2} ≤ 27 W 220 k_Ω,
W_{a+g2} > 27 W 100 k_Ω,
Capacitances:
c_{g1} = 16 pF
c_a = 10 pF
c_{a/g1} = 2,3 pF

Productinformatie

Artikelnummer	KT66
Merk	JJ ELECTRONIC
Is on Sale	Nee

