

EINDBUIS 8P OKTAL OUTPUT PENTODE

€ 39,95

Excl. BTW: € 33,02

Afbeeldingen



Beschrijving

A. F. OUTPUT PENTODE

Base: OCTAL

U<sub>f</sub> = 6,3 V

I<sub>f</sub> = ca 1,5 A

Typical

characteristic:

U<sub>a</sub> = 250 V

Ug3 = 0 V  
Ug2 = 265 V  
Ug1 = -10 V; -13,5 V  
(for EL34)  
-13,5 V; -16,5 V  
(for E34L)  
Ia = 100 mA  
Ig2 = 14,9 mA  
S = 11 mA/V  
Ri = 15 kΩ  
ig2/g1 = 11  
Iaz (Ug1 = -30 V) < 7 mA  
Limiting values:  
Ua0 = 2000 V  
Ua = 800 V  
Wa(max) = 25 W  
Ug20 = 800 V  
Ug2 = 450 V  
Wg2(max) = 8 W  
Ik = 150 mA  
Uk/f = 100 V  
Rk/f = 20 kΩ  
Capacitances:  
cg1 = 15,5 pF  
ca = 10 pF  
ca/g1 = 1,3 pF

## Productinformatie

---

Artikelnummer	EL34
Merk	JJ ELECTRONIC
Is on Sale	Nee

