


GESCHAKELDE VOEDING 40W 12V/3,33A IP64

€ 49,50

Excl. BTW: € 40,91

Afbeeldingen



Beschrijving

Features

- Universal input
- Overload protection, current limiting, auto recovery
- Protections: short circuit/over load/over voltage
- Built-in active PFC function
- IP64, for indoor and outdoor installations
- Suitable for LED lighting and moving sign applications
- Adjustable output voltage
- Adjustable output current
- EN61000-3-2, Class C, EN55015, EN61347-1, EN61347-2-13

Technical Specifications

Input Voltage: 90...305V AC (47...63Hz)/ 127...431V DC
Input Inrush Current, Max.: 70A
Over Current Protection: 95...108%
Withstand Voltage
I/P-O/P: 3750V AC

I/P-FG: 1880V AC
O/P-FG: 500V AC
Operating Temperature: -40...+50°C
Weight: 350g
I/P = Input, O/P = Output, FG = Frame Ground

Output Voltage: 12V
Output Voltage Adjustment: 10,8...13,5V
Output Current Adjustment: 2...3,33A
Output Power: 40W
Output Voltage Tolerance: 2,5%
Ripple & Noise:150mVp-p
Typ. Efficiency: 87%

Productinformatie

Artikelnummer	HLN40H12A
Merk	MEANWELL
Is on Sale	Nee

