

## DC-DC CONVERTER 36-72V:24V 2.1A IN BEHUIZING

€ 44,95

Excl. BTW: € 37,15

### Afbeeldingen



### Beschrijving

2:1 wide input range  
Protections: Short circuit / Overload / Over voltage  
1500VDC I/O isolation  
Built-in EMI filter, low ripple noise  
100% full load burn-in test  
Fixed switching frequency at 83KHz  
Low cost  
High reliability

#### OUTPUT

DC VOLTAGE: 24V  
RATED CURRENT: 2,1A  
CURRENT RANGE: 0 ~ 2.1A  
RATED POWER: 50.4W  
RIPPLE & NOISE (max.) Note.2: 150mVp-p  
VOLTAGE ADJ. RANGE: 23 ~ 30VDC  
VOLTAGE TOLERANCE Note.3: +/- 1.0%

LINE REGULATION: +/- 0.2%  
LOAD REGULATION: +/- 0.2%  
SETUP, RISE, HOLD UP TIME: 2.5s, 50ms, ----- at full load

INPUT  
VOLTAGE RANGE: 38 ~ 72VDC  
INPUT EFFICIENCY (Typ.): 83%  
DC CURRENT: 1.5A/48V

DIMENSION: 159x97x38mm (LxWxH)

## Productinformatie

---

Artikelnummer	SD50C24
Merk	MEANWELL
Is on Sale	Nee

