

GESCHAKELDE VOEDING 9.9W 3.3V/3A

€ 13,95

Excl. BTW: € 11,53

Afbeeldingen



Beschrijving

Universal AC input / Full range
Protections: Short circuit / Overload / Over voltage / Over temperature
Cooling by free air convection
LED indicator for power on
100% full load burn-in test
All using 105C long life electrolytic capacitors
Withstand 300VAC surge input for 5 second
High operating temperature up to 70
Withstand 5G vibration test
High efficiency, long life and high reliability

MODEL RS-15-3.3
OUTPUT:
DC VOLTAGE 3.3V
RATED CURRENT 3A

CURRENT RANGE 0 ~ 3A
RATED POWER 9.9W
RIPPLE & NOISE (max.) 80mVp-p
OUTPUT VOLTAGE ADJ. RANGE 2.9 ~ 3.6V
VOLTAGE TOLERANCE +/-3.0%
LINE REGULATION +/-0.5%
LOAD REGULATION +/-2.0%
SETUP, RISE TIME 1000ms, 30ms/230VAC
HOLD TIME (Typ.) 70ms/230VAC at full load

INPUT:

VOLTAGE RANGE 88 ~ 264VAC
FREQUENCY RANGE 47 ~ 63Hz
EFFICIENCY(Typ.) 77%
AC CURRENT (Typ.) 0.35A/230VAC
INRUSH CURRENT (Typ.) COLD START 65A/230VAC
LEAKAGE CURRENT <2mA / 240VAC

PROTECTION:

OVER LOAD Above 105% rated output power
Protection type : Hiccup mode, recovers automatically after fault condition is
OVER VOLTAGE 5.75 ~ 6.75V
Protection type : Shut down o/p voltage, recovers automatically after temperature goes down
Dimensions 99*82*36mm (L*W*H)

Productinformatie

Artikelnummer	RS1503
Merk	MEANWELL
Is on Sale	Nee

