

DIN-RAIL 22.5MM VOEDING 15W 5V/3.0A

€ 18,95

Excl. BTW: € 15,66

Afbeeldingen



Beschrijving

MODEL MDR-20-5

OUTPUT:

DC VOLTAGE 5V

RATED CURRENT 3A

CURRENT RANGE 0~ 3.0A

RATED POWER 15W

RIPPLE & NOISE (max.) Note.2 80mVp-p

VOLTAGE ADJ. RANGE 4.74-5.5V

VOLTAGE TOLERANCE Note.3 +/-2.0%

LINE REGULATION +/-1.0%

LOAD REGULATION +/-1.0%

SETUP, RISE TIME 500ms, 30ms/230VAC at full load

HOLD UP TIME (Typ.) 50ms/230VAC at full load

INPUT:

VOLTAGE RANGE 85 ~ 264VAC

FREQUENCY RANGE 47 ~ 63Hz

EFFICIENCY (Typ.) 76%
AC CURRENT (Typ.) 0.35A/230VAC
INRUSH CURRENT (Typ.) COLD START 40A/230VAC
LEAKAGE CURRENT <1mA / 240VAC

PROTECTION:

OVERLOAD

105 ~ 160% rated output power

Protection type : Constant current limiting, recovers automatically after fault condition is removed

OVER VOLTAGE 5.75-6.75V

Protection type : Shut down o/p voltage, re-power on to recover.

FUNCTION DC OK SIGNAL (max.) 3.75-6V/50mA

DIMENSION: 22.5*90*100mm (W*H*D)

Productinformatie

Artikelnummer	MDR205
Merk	MEANWELL

