

DIN-RAIL 22.5MM VOEDING 10W 12V/0.84A

€ 16,95

Excl. BTW: € 14,01

Afbeeldingen



Beschrijving

- Universal AC input/Full range
- Protections: Short circuit / Overload / Over voltage
- Cooling by free air convection
- Can be installed on DIN rail TS-35/7.5 or 15
- NEC class 2 / LPS compliant
- Built in DC OK active signal
- LED indicator for power on
- No load power consumption<0.75W

100% full load burn-in test

#### Technical Specifications

Input Voltage: 85...264V AC (47...63Hz) 120...370V DC

Input Inrush Current, Max.: 70A

Leakage Current, Max.: 1mA

No Load Power Consumption, Max.: 0,75W

Over Load Protection: >105%

Withstand Voltage

I/P-O/P: 3000V AC

I/P-FG: 1500V AC

O/P-FG: 500V AC

Operating Temperature: -20...+70°C

uitgangsspanning: 12V +/-3%

uitgangsstroom: 0.84A

max. vermogen: 10W

afmetingen: 22.5 x 90 x 100mm

gewicht: 170g

werktemperatuur: -20°C ~ 70°C

#### Productinformatie

---

Artikelnummer	MDR1012
Merk	MEANWELL
Is on Sale	Nee

