

**GESCHAKELDE VOEDING SINGLE OUTPUT 60W 5.0V/12A**

**€ 31,50**

Excl. BTW: € 26,03

**Afbeeldingen**



**Beschrijving**

MODEL RS-75-5

OUTPUT:

DC VOLTAGE 5V

RATED CURRENT 12A

CURRENT RANGE 0 - 12A

RATED POWER 60W

RIPPLE & NOISE (max.) 80mVp-p

OUTPUT VOLTAGE ADJ. RANGE 4.75 ~ 5.5V

VOLTAGE TOLERANCE +/-2.0%

LINE REGULATION +/-0.5%

LOAD REGULATION +/-1.0%  
SETUP, RISE TIME 500ms, 30ms/230VAC  
HOLD TIME (Typ.) 60ms/230VAC at full load

INPUT:

VOLTAGE RANGE 88 ~ 264VAC  
FREQUENCY RANGE 47 ~ 63Hz  
EFFICIENCY(Typ.) 76%  
AC CURRENT (Typ.) 1.2A/230VAC  
INRUSH CURRENT (Typ.) COLD START 40A/230VAC  
LEAKAGE CURRENT <2mA / 240VAC

PROTECTION:

OVER LOAD 110 ~ 150% rated output power  
Protection type : Hiccup mode, recovers automatically after fault condition is removed  
OVER VOLTAGE 5.75 ~ 6.75V Protection type : Hiccup mode, recovers automatically after fault condition is removed

Dimensions 129\*97\*38mm (L\*W\*H)

## Productinformatie

---

Artikelnummer	RS7505
Merk	MEANWELL
Is on Sale	Nee

