

LED VOEDING 12V/13.00A 156W IP65 BEHUIZING

€ 79,94

Excl. BTW: € 66,07

Afbeeldingen



Beschrijving

- Universal AC input / Full range (up to 305VAC)
- Built-in active PFC function
- Protections: Short circuit / Over / Over voltage / Over temperature
- Cooling by free air convection
- OCP point adjustable through output cable or internal
- IP67 / IP65 design for indoor or outdoor installations
- Three in one dimming function (1-10Vdc or PWM signal or
- Suitable for LED lighting and street lighting applications
- Compliance to worldwide safety regulations for lighting
- IP65 rated. Output voltage and constant current level can be adjusted through internal potentiometer.

Input Voltage: 90...305V AC (47...63Hz)

Input Inrush Current, Max.: 75A

Over Current Protection: 95...108%

Withstand Voltage

I/P-O/P: 3750V AC
I/P-FG: 2000V AC
O/P-FG: 500V AC
Operating Temperature: -40...+50°C
Weight: 1250g
I/P = Input, O/P = Output, FG = Frame Ground

Output Voltage: 12V
Output Voltage Adjustment: 10,8...13,527V
Output Current Adjustment: 6,5...13A
Output Power: 156W
Output Voltage Tolerance: 2,5%
Ripple & Noise: 150mVp-p
Typ. Efficiency: 91,5%

Productinformatie

Artikelnummer	HLG185H12A
Merk	MEANWELL
Is on Sale	Nee

