

LED VOEDING 30V/8A 240W IP65 BEHUIZING

€ 99,00

Excl. BTW: € 81,82

Afbeeldingen



Beschrijving

Universal AC input / Full range

Built-in active PFC function

Protections: Short circuit / Over current / Over voltage / Over temperature

Cooling by free air convection

OCP point adjustable through output cable or internal potentiometer

IP67 / IP65 design for indoor or outdoor installations

Type HL LED Driver for use in Class C₁, Division 2 hazardous location luminaires

Three in one dimming function (1~10Vdc or PWM signal or resistance)

Suitable for LED lighting and street lighting applications

Compliance to worldwide safety regulations for lighting

Suitable for dry / damp / wet locations

Uitgang

dc spanning : 30V

Stroom (max.) : 8A

Vermogen : : 240W

Ripple & Noise (max.) : 200mVp-p

Spanning instelbaar : 28 ~ 32V

IP-classificatie : IP65

Adjustable output voltage with internal potentiometer

Adjustable output current with internal potentiometer

Ingang spanning : 90 ~ 264VAC 127 ~ 373VDC

Frequentie : 47 ~ 63Hz

Productinformatie

Artikelnummer	HLG24030A
Merk	MEANWELL
Is on Sale	Nee

