

DIN-RAIL 40MM VOEDING 60W 24V/2.5A

€ 25,95

Excl. BTW: € 21,45

Afbeeldingen



Beschrijving

MODEL MDR-60-24

OUTPUT:

DC VOLTAGE 24V

RATED CURRENT 2.5A

CURRENT RANGE 0~ 2.5A

RATED POWER 60W

RIPPLE & NOISE (max.) Note.2 150mVp-p

VOLTAGE ADJ. RANGE 24~30V

VOLTAGE TOLERANCE Note.3 +/-1.0%

LINE REGULATION +/-1.0%

LOAD REGULATION +/-1.0%

SETUP, RISE TIME 500ms, 30ms/230VAC at full load

HOLD UP TIME (Typ.) 50ms/230VAC at full load

INPUT:

VOLTAGE RANGE 85 ~ 264VAC

FREQUENCY RANGE 47 ~ 63Hz

EFFICIENCY (Typ.) 88%

AC CURRENT (Typ.) 1A/230VAC

INRUSH CURRENT (Typ.) COLD START 36A/230VAC
LEAKAGE CURRENT <1mA / 240VAC

PROTECTION:

OVERLOAD

105 ~ 150% rated output power

Protection type : Constant current limiting, recovers automatically after fault condition is removed

OVER VOLTAGE 31.2 ~ 36V

Protection type : Shut down o/p voltage, re-power on to recover.

FUNCTION DC OK SIGNAL Relay contact rating(max.): 30V/1A resistive

DIMENSION: 40*90*100mm (W*H*D)

Productinformatie

Artikelnummer	MDR6024
Merk	MEANWELL
Is on Sale	Nee

