

DIODE SCHOTTKY 100V 10A TP220AC

€ 1,63

Excl. BTW: € 1,35

Afbeeldingen



Beschrijving

Features

Plastic material used carries Underwriters Laboratory

Classifications 94V-0

Metal silicon junction, majority carrier conduction

Low power loss, high efficiency

High current capability, low forward voltage drop

High surge capability

For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications

Guardring for overvoltage protection

High temperature soldering guaranteed:

250oC/10 seconds, 0.25" (6.35mm) from case

Mechanical Data

Cases: JEDEC TO-220A molded plastic body

Terminals: Lead solderable per MIL-STD-750, Method 2026

Polarity: As marked

Mounting position: Any

Mounting torque: 5 in. - lbs. max

Weight: 0.08 ounce, 2.24 grams

Maximum Recurrent Peak Reverse Voltage 100 V

Maximum RMS Voltage 70 V

Maximum DC Blocking Voltage 100 V

Maximum Average Forward Rectified Current at Tc=125OC 10 A

Peak Repetitive Forward Current (Rated VR, Square Wave, 20KHz) at Tc=125oC 32.0 A

Productinformatie

Artikelnummer	MBR10100
Merk	Merk

