

ADAPTER 18V 300MA GESCHAKELD

€ 18,95

Excl. BTW: € 15,66

Afbeeldingen



Beschrijving

Features

- Plug-in switching power supply
- Universal AC input
- Class II power (without earth pin)
- Compact design
- Overload and short circuit protection

Technical Specifications

- Operating Temperature: 0...+40°C
- Storage Temperature: -20...+85°C
- MTBF: 50.000h/25°C
- Dimensions: 32x66x42,5mm
- Weight: 100g
- Cable Length: 1,8m
- Plug: Coaxial Plug

Ø2,1 inner(+) x Ø5,5 outer(-)

Input

Input Voltage: 90...264V AC (47...63Hz)

Conducted Interference: EN 55022 (B)

EN61000-3-2,-3-3,-4-2,-4-3,-4-4,-4-5,-4-6,-4-8,-4-11

Hold Up Time, 115V: 16ms

In-Rush Current 230V: 30A

Output Voltage, 18V

Output Voltage Tolerance 3%

Ripple & Noise, 100mV

Output Rated Current, 300mA

DC Output Power, 6W

Efficiency, 78%

All Technical Specifications are Applicable to TU = 25°

Productinformatie

Artikelnummer	PSS1803
Merk	MEANWELL
Is on Sale	Nee

