

DC-DC CONVERTER 36-72V:5V 10.0A IN BEHUIZING

€ 44,95

Excl. BTW: € 37,15

Afbeeldingen



Beschrijving

2:1 wide input range
Protections: Short circuit / Overload / Over voltage
1500VDC I/O isolation
Built-in EMI filter, low ripple noise
100% full load burn-in test
Fixed switching frequency at 83KHz
Low cost
High reliability

OUTPUT

DC VOLTAGE: 5V
RATED CURRENT: 10A
CURRENT RANGE: 0 ~ 10A
RATED POWER: 50W
RIPPLE & NOISE (max.) Note.2: 100mVp-p
VOLTAGE ADJ. RANGE: 4.5 ~ 5.5VDC
VOLTAGE TOLERANCE Note.3: +/- 2.0%

LINE REGULATION: +/- 0.5%
LOAD REGULATION: +/- 0.5%
SETUP, RISE, HOLD UP TIME: 2.5s, 50ms, ----- at full load

INPUT
VOLTAGE RANGE: 36 ~ 72VDC
INPUT EFFICIENCY (Typ.): 76%
DC CURRENT: 3A/24V

DIMENSION: 159x97x38mm (LxWxH)

Productinformatie

Artikelnummer	SD50C5
Merk	MEANWELL
Is on Sale	Nee

