

DC-DC CONVERTER 18-36V:12V 2.1A IN BEHUIZING

€ 34,50

Excl. BTW: € 28,51

Afbeeldingen



Beschrijving

25W Single Output DC-DC Converter
2:1 wide input range
Protections: Short circuit / Overload / Over voltage
1500VDC I/O isolation
Built-in EMI filter, low ripple noise
100% full load burn-in test
Fixed switching frequency at 83KHz
Low cost
High reliability

OUTPUT

DC VOLTAGE: 12V
RATED CURRENT: 2,1A
CURRENT RANGE: 0 ~ 2.1A
RATED POWER: 25.2W
RIPPLE & NOISE (max.) Note.2: 120mVp-p
VOLTAGE ADJ. RANGE: 11 ~ 16VDC
VOLTAGE TOLERANCE Note.3: +/- 1.0%
LINE REGULATION: +/- 0.3%
LOAD REGULATION: +/- 0.3%
SETUP, RISE, HOLD UP TIME: 2.5s, 50ms, ----- at full load

INPUT

VOLTAGE RANGE: 19 ~ 36VDC
INPUT EFFICIENCY (Typ.): 75%
DC CURRENT: 1.6A/24V

DIMENSION: 99x97x36mm (LxWxH)

Productinformatie

Artikelnummer	SD25B12
Merk	MEANWELL
Is on Sale	Nee

