
PLAFONDSPEAKER 1,5W/3W/6W 100V 170MM (RAL 9016)

€ 47,50

Excl. BTW: € 39,26

Afbeeldingen



Beschrijving

17 cm (6.5") ceiling speaker with corrosion free grille (RAL 9016), suitable for the installation in suspended ceilings of any material. Equipped with a full-range driver. Quick snap-in mounting due to round ceiling cut-out through which the speaker with transformer and mounting ring can be installed. A push-terminal block allows a quick and easy connection to the 100-V-network including the eventually necessary level adjustment. A quick-mounting bayonet connection provides an easy installation of the grille.

DL 18/1 can be supplied painted in other RAL colours on request.

Speaker cabinet systems for ceilings are available for these speakers from KAISER, 58579 Schalksmühle, Germany. The KompaX cabinet is suitable for the DL 18/1 and DL 18/2, Art. nos. 1293-15, 1293-00, 1292-35, 1292-00, 1294-15 and 1294-00 in conjunction with the front ring Art. no. 1293-20. Fire protection housing systems (F30) are available (FlamoX).

Typical applications:

- For fitting in hollow ceilings, for music and speech in shops, at home, hotels etc.

Attributes:

- Moisturised cone
- UV-resistant
- Metal basket, non-corrodible
- functionally at low temperature according to EN 60068-2-1 (-40 °C; 96 h)
- up to the standards of the Germanischer Lloyd (requirements for electrical equipment / low temperature)

Transformer matching 6; 3; 1,5 W
Sound pressure level 101 dB (1 W/1 m)
@ 3260 Hz
Frequency response 70- 20000 Hz
Mean sound pressure level 93 dB (1 W/1 m)
Max. sound pressure level 101 dB (6 W/1 m)
Opening angle (-6 dB) 57°/4000 Hz
Resonance frequency fs 100 Hz
Voice coil diameter 20 mm
Cutout diameter 200 mm
Net weight 1,15 kg
Protective system IP X3
Temperature range -40 ... 110 °C
Colour RAL 9016

Productinformatie

Artikelnummer	DL18/1R
Merk	VISATON
Is on Sale	Nee

