

PLAFONDSPEAKER 3/1,5/0,75W 100V

€ 45,00

Excl. BTW: € 37,19

Afbeeldingen



Beschrijving

8 cm (3.3") ceiling-mounted speaker with white metal cover (RAL 9010). Suitable for use in all types of hollow ceilings. Easy fitting in round cut-out using spring arms, electrical connection by spring-loaded terminal clips. A compact solution for home and professional use with good sound qualities. Smaller voice coil enlarges the sound pressure level.

DL 8 can be supplied painted in other RAL colours on request.

Speaker cabinet systems for ceilings are available for these speakers from KAISER, 58579 Schalksmühle, Germany. The KompaX cabinet is suitable for the DL 8, Art. nos. 1292-35, 1292-00, 1294-15 and 1294-00 in conjunction with the front ring Art. no. 1292-01. Fire protection housing systems (F30) are available (FlamoX).

Typical applications:

- For fitting in hollow ceilings, for music and speech in shops, at home, hotels etc.

Attributes:

- Moisturised cone
- UV-resistant
- Metal basket, non-corrodible
- functionally at low temperature according to EN 60068-2-1 (-40 °C; 96 h)
- up to the standards of the Germanischer Lloyd (requirements for electrical equipment / low temperature)
- Ball-resistant
- 100 V transformer

Transformer matching 3; 1,5; 0,75 W
Sound pressure level 90 dB (1 W/1 m)
@ 3600 Hz
Frequency response 90- 18000 Hz
Mean sound pressure level 87 dB (1 W/1 m)
Max. sound pressure level 91 dB (3 W/1 m)
Opening angle (-6 dB) 112°/4000 Hz
Height of front pole-plate 3 mm
Voice coil diameter 14 mm
Cutout diameter 93 mm
Net weight 0,515 kg
Length of cable 0,15 m
Protective system IP 54 *)
Temperature range -40 ... 110 °C
Colour RAL 9010

Productinformatie

Artikelnummer	DL8/1
Merk	VISATON
Is on Sale	Nee

