

## DIN-RAIL VOEDING 40MM 120W 24V/5A

€ 79,50

Excl. BTW: € 65,70

### Afbeeldingen



### Beschrijving

Single and two phase wide input range 180 ~ 550VAC  
Protections: Short circuit / Overload / Over voltage / Over temperature  
Cooling by free air convection  
Built-in constant current limiting circuit  
Can be installed on DIN rail TS-35/7.5 or 15  
EN61000-6-2(EN50082-2) industrial immunity level  
100% full load burn-in test  
Built-in UL508(industrial control equipment)approved  
DC OK relay contact

OUTPUT:

DC VOLTAGE 24V

RATED CURRENT 5A

CURRENT RANGE 0 ~ 5A

RATED POWER 120W

RIPPLE & NOISE (max.) 120mVp-p

OUTPUT VOLTAGE ADJ. RANGE 24 ~ 29V

VOLTAGE TOLERANCE +/-1.0%

INPUT:

VOLTAGE RANGE 180 ~ 550VAC 254 ~ 780VDC

FREQUENCY RANGE 47 ~ 63Hz

40x125.2x113.5mm (W\*H\*D)

## Productinformatie

---

Artikelnummer	WDR12024
Merk	MEANWELL
Is on Sale	Nee

