

GESCHAKELDE VOEDING SINGLE OUTPUT 76W 48V/1.6A

€ 31,50

Excl. BTW: € 26,03

Afbeeldingen



Beschrijving

MODEL RS-75-48

OUTPUT:

DC VOLTAGE 48V

RATED CURRENT 1.6A

CURRENT RANGE 0 ~ 1.6A

RATED POWER 76.8W

RIPPLE & NOISE (max.) 200mVp-p

OUTPUT VOLTAGE ADJ. RANGE 42 ~ 54V

VOLTAGE TOLERANCE +/-1.0%

LINE REGULATION +/-0.5%

LOAD REGULATION +/-0.5%
SETUP, RISE TIME 500ms, 30ms/230VAC
HOLD TIME (Typ.) 60ms/230VAC at full load

INPUT:

VOLTAGE RANGE 88 ~ 264VAC
FREQUENCY RANGE 47 ~ 63Hz
EFFICIENCY(Typ.) 86%
AC CURRENT (Typ.) 1.2A/230VAC
INRUSH CURRENT (Typ.) COLD START 40A/230VAC
LEAKAGE CURRENT <2mA / 240VAC

PROTECTION:

OVER LOAD 110 ~ 150% rated output power
Protection type : Hiccup mode, recovers automatically after fault condition is removed
OVER VOLTAGE 55.2 ~ 64.8V Protection type : Hiccup mode, recovers automatically after fault condition is removed

Dimensions 129*97*38mm (L*W*H)

Productinformatie

Artikelnummer	RS7548
Merk	MEANWELL
Is on Sale	Nee

