

MEERPOLIG STEKER 6P FEMALE IP68

€ 9,95

Excl. BTW: € 8,22

Afbeeldingen



Contact arrangement and open for solder terminals						
Pin	1	2	3	4	5	6
With contact key (mm)	1.5	1.5	1.5	1.5	1.5	1.5
Pin diameter (mm)	0.8	0.8	0.8	0.8	0.8	0.8
Pin length (mm)	1.5	1.5	1.5	1.5	1.5	1.5
Pin spacing (mm)	2.5	2.5	2.5	2.5	2.5	2.5
Pin length (mm)	1.5	1.5	1.5	1.5	1.5	1.5
Pin length (mm)	1.5	1.5	1.5	1.5	1.5	1.5
Pin length (mm)	1.5	1.5	1.5	1.5	1.5	1.5
Pin length (mm)	1.5	1.5	1.5	1.5	1.5	1.5
Pin length (mm)	1.5	1.5	1.5	1.5	1.5	1.5

Beschrijving

Features

- Cliffcon® 68 is an IP68 rated multipin connector for waterproof and rugged applications
- IP68 for under water, outdoor and indoor
- 2 to 9 gold-plated contacts (no 8 pin version)
- Fixing thread M15
- Panel hole cut-out 13mm Ø
- FM 686800: sealing cap for socket FM68680_ (must be ordered separately)



Technical Specifications



Connector Locking System:

Screw

Connection Type	Solder
Degree of Protection:	IP68
Mechanical Operating Life, Min.:	500 Cycles
Temperature Range:	-25...+85°C
Insulation Resistance:	20000Ohm
Material of Contact:	CuZn, Gold-plated
Material of Housing:	Nylon 66 ¹⁾
Cable Diameter (Female Plug):	5...8mm

¹⁾fire resistance: V-O



Socket	Pole	U _N	I _N	Contact Ø	R _C
	[A]	[V AC]	[A]	[mm]	[Ohm]
FM686802	2	250	13	1,6x2	2
FM686803	3	250	13	1,6x3	2
FM686804	4	200	5	1x4	5
FM686805	5	180	5	1x5	5
FM686806	6	125	5	1x6	5
FM686807	7	125	5	1y7	5
FM686809	9	125	3	0,7x9	10

U_N = Rated Voltage, I_N = Rated Current, R_C = Contact Resistance

Productinformatie

Artikelnummer	FM686816
Merk	CLIFF
Is on Sale	Nee

