

MEERPOLIG CHASSIS 5P MALE IP68

€ 8,95

Excl. BTW: € 7,40

Afbeeldingen



Contact arrangement and open bracket configurations

Configuration	1	2	3	4	5
Male contact face view					
Pin positions (mm)	0	12.5	25	37.5	50
Pin diameters (mm)	Ø 1.27	Ø 1.27	Ø 1.27	Ø 1.27	Ø 1.27
Pin lengths (mm)	20.00	20.00	20.00	20.00	20.00
Pin diameters (mm)	Ø 1.27	Ø 1.27	Ø 1.27	Ø 1.27	Ø 1.27
Pin lengths (mm)	20.00	20.00	20.00	20.00	20.00
Pin diameters (mm)	Ø 1.27	Ø 1.27	Ø 1.27	Ø 1.27	Ø 1.27
Pin lengths (mm)	20.00	20.00	20.00	20.00	20.00

Beschrijving

SPECIFICATION

Coupling Type Threaded coupling

IP Rating IP68

Material Plastic Shell

Nylon66, fire resistance:V-0

Insert material PPS max temperature 260°C, fire resistance:V-0

Contact material Brass with gold plating

Termination Solder

Cable OD 5-8mm

Mating cycle > 500

Temperature range -25~+85°C

Insulation resistance 2000MΩ

Productinformatie

Artikelnummer	FM686805
Merk	CLIFF

