

MEERPOLIG CHASSIS 7P MALE IP68

€ 8,95

Excl. BTW: € 7,40

Afbeeldingen



Contact arrangement and open bracket configurations

Configuration	1	2	3	4	5	6	7
Male contact face view	⊙	⊙	⊙	⊙	⊙	⊙	⊙
Bracket view (1)	⊙	⊙	⊙	⊙	⊙	⊙	⊙
Bracket view (2)	⊙	⊙	⊙	⊙	⊙	⊙	⊙
Bracket view (3)	⊙	⊙	⊙	⊙	⊙	⊙	⊙
Bracket view (4)	⊙	⊙	⊙	⊙	⊙	⊙	⊙
Bracket view (5)	⊙	⊙	⊙	⊙	⊙	⊙	⊙
Bracket view (6)	⊙	⊙	⊙	⊙	⊙	⊙	⊙
Bracket view (7)	⊙	⊙	⊙	⊙	⊙	⊙	⊙
Bracket view (8)	⊙	⊙	⊙	⊙	⊙	⊙	⊙

Beschrijving

SPECIFICATION

Coupling Type Threaded coupling

IP Rating IP68

Material Plastic Shell

Nylon66, fire resistance:V-0

Insert material PPS max temperature 260°C, fire resistance:V-0

Contact material Brass with gold plating

Termination Solder

Cable OD 5-8mm

Mating cycle > 500

Temperature range -25~+85°C

Insulation resistance 2000MΩ

Productinformatie

Artikelnummer	FM686807
Merk	CLIFF

