

MEERPOLIG STEKER 2P FEMALE IP68

€ 9,50

Excl. BTW: € 7,85

Afbeeldingen



| Cliffcon 68 | 2P | 3P | 4P | 5P | 6P | 7P | 8P | 9P |
|-------------------------|-----|-----|-----|-----|-----|-----|-----|-----|
| Max contact force (N) | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 10 |
| Retention (N) | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 10 |
| Contact resistance (mΩ) | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 |
| Max. voltage (V AC) | 250 | 250 | 250 | 250 | 250 | 250 | 250 | 250 |
| Max. voltage (V DC) | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 |
| Current (A) | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 |
| Max. cable length (m) | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 10 |

Beschrijving

Features

- Cliffcon® 68 is an IP68 rated multipin connector for waterproof and rugged applications
- IP68 for under water, outdoor and indoor
- 2 to 9 gold-plated contacts (no 8 pin version)
- Fixing thread M15
- Panel hole cut-out 13mm Ø
- FM 686800: sealing cap for socket FM68680_ (must be ordered separately)



Technical Specifications



Connector Locking System:

Screw

| | |
|----------------------------------|------------------------|
| Connection Type | Solder |
| Degree of Protection: | IP68 |
| Mechanical Operating Life, Min.: | 500 Cycles |
| Temperature Range: | -25...+85°C |
| Insulation Resistance: | 20000hm |
| Material of Contact: | CuZn, Gold-plated |
| Material of Housing: | Nylon 66 ¹⁾ |
| Cable Diameter (Female Plug): | 5...8mm |

¹⁾fire resistance: V-O



| Socket | Pole | U_N | I_N | Contact Ø | R_C |
|----------|------|--------|-------|-----------|-------|
| | [A] | [V AC] | [A] | [mm] | [Ohm] |
| FM686802 | 2 | 250 | 13 | 1,6x2 | 2 |
| FM686803 | 3 | 250 | 13 | 1,6x3 | 2 |
| FM686804 | 4 | 200 | 5 | 1x4 | 5 |
| FM686805 | 5 | 180 | 5 | 1x5 | 5 |
| FM686806 | 6 | 125 | 5 | 1x6 | 5 |
| FM686807 | 7 | 125 | 5 | 1y7 | 5 |
| FM686809 | 9 | 125 | 3 | 0,7x9 | 10 |

U_N = Rated Voltage, I_N = Rated Current, R_C = Contact Resistance

Productinformatie

| | |
|---------------|----------|
| Artikelnummer | FM686812 |
| Merk | CLIFF |

