

MEERPOLIG STEKER 4P FEMALE IP68

€ 9,95

Excl. BTW: € 8,22

Afbeeldingen



Cliffcon 68	2	3	4	5	6	7	8	9
Max contact size (mm)	1.27	1.27	1.27	1.27	1.27	1.27	1.27	1.27
Panel thickness (mm)	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0
Panel hole cut-out (mm)	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.0
Max contact pitch (mm)	2.54	2.54	2.54	2.54	2.54	2.54	2.54	2.54
Max contact pitch (mm)	2.54	2.54	2.54	2.54	2.54	2.54	2.54	2.54
Max contact pitch (mm)	2.54	2.54	2.54	2.54	2.54	2.54	2.54	2.54
Max contact pitch (mm)	2.54	2.54	2.54	2.54	2.54	2.54	2.54	2.54

Beschrijving

Features

- Cliffcon® 68 is an IP68 rated multipin connector for waterproof and rugged applications
- IP68 for under water, outdoor and indoor
- 2 to 9 gold-plated contacts (no 8 pin version)
- Fixing thread M15
- Panel hole cut-out 13mm Ø
- FM 686800: sealing cap for socket FM68680_ (must be ordered separately)



Technical Specifications



Connector Locking System:

Screw

Connection Type	Solder
Degree of Protection:	IP68
Mechanical Operating Life, Min.:	500 Cycles
Temperature Range:	-25...+85°C
Insulation Resistance:	20000hm
Material of Contact:	CuZn, Gold-plated
Material of Housing:	Nylon 66 ¹⁾
Cable Diameter (Female Plug):	5...8mm

¹⁾fire resistance: V-O



Socket	Pole	U_N	I_N	Contact Ø	R_C
	[A]	[V AC]	[A]	[mm]	[Ohm]
FM686802	2	250	13	1,6x2	2
FM686803	3	250	13	1,6x3	2
FM686804	4	200	5	1x4	5
FM686805	5	180	5	1x5	5
FM686806	6	125	5	1x6	5
FM686807	7	125	5	1y7	5
FM686809	9	125	3	0,7x9	10

U_N = Rated Voltage, I_N = Rated Current, R_C = Contact Resistance

Productinformatie

Artikelnummer	FM686814
Merk	CLIFF

