

## GESCHAKELDE VOEDING SINGLE OUTPUT 26W 24V/1.1A

€ 16,50

Excl. BTW: € 13,64

### Afbeeldingen



### Beschrijving

#### Note

These power supplies are considered as a component that has to be installed in a final equipment.



#### Features

- Enclosed case, screw terminals
- Universal input
- Overload protection, pulsing hiccup shutdown, auto recovery
- Protections: short circuit/over load/over voltage
- Long life 105°C electrolytic capacitors



#### Technical Specifications



Input Voltage:	88...264V AC (47...63Hz)
	125...373V DC
Input Inrush Current, Max.:	30A
Leakage Current, Max.:	2mA
Output Voltage Adjustment:	+10/-5%
Over Load Protection:	110...180%
Withstand Voltage	
I/P-O/P:	3000V AC
I/P-FG:	2000V AC
O/P-FG:	500V AC
Operating Temperature:	-20...+70°C
Weight:	200g

I/P = Input, O/P = Output, FG = Frame Ground



Part Nr.	$U_A$	$I_A$	$P_A$	$DU_A$	$U_{RN}$	$h$
	[V]	[A]	[W]	[%]	[mV <sub>p-p</sub> ]	[%]
RS-25-3.3	3,3	0...6	19,8	3	80	73,5
RS-25-5	5	0...5	25	2	80	78,5
RS-25-12	12	0...2,1	25,2	1	120	81,5
RS-25-15	15	0...1,7	25,5	1	120	83,5
RS-25-24	24	0...1,1	26,4	1	120	86
RS-25-48	48	0...0,57	27,36	1	200	85

$U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise,  $h$  = Efficiency



Labelling





## Productinformatie

---

Artikelnummer	RS2524
Merk	MEANWELL

