


## LED DRIVER 24-48V/3150MA 150W IP67 BEHUIZING

€ 49,95

Excl. BTW: € 41,28

### Afbeeldingen



### Beschrijving

#### Features

- Universal input
- Plastic enclosure IP67
- Overload protection, current limiting, auto recovery
- Protections: short circuit/over load/over voltage
- Protection Class 2
- Fixed output current



#### Technical Specifications



Input Voltage:	180...305V AC (47...63Hz)
	254...431V DC
Input Inrush Current, Max.:	40A
Withstand Voltage (I/P-O/P):	3000V AC
Operating Temperature:	-25...+50°C
Weight:	740g

I/P = Input, O/P = Output



Part Nr.	$U_A$	$I_A$	$P_A$	$DI_A$	$U_{RN}$	$h$
	[V]	[mA]	[W]	[%]	[V <sub>p-p</sub> ]	[%]
LPC-150-350	215...430	350	150,5	5	2	90
LPC-150-500	150...300	500	150	5	1,5	90
LPC-150-700	107...215	700	150,5	5	1	90
LPC-150-1050	72...144	1050	151,2	5	1	90
LPC-150-1400	54...108	1400	151,2	5	1	90
LPC-150-1750	43...86	1750	150,5	5	1	90
LPC-150-2100	36...72	2100	151,2	5	1	90
LPC-150-2450	31...62	2450	151,9	5	1	90
LPC-150-2800	27...54	2800	151,2	5	1	90
LPC-150-3150	24...48	3150	151,2	5	1	90

$U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $DI_A$  = Output Current Tolerance,  $U_{RN}$  = Ripple & Noise,  $h$  = Typ. Efficiency



Note

Devices only for use in equipment with another primary purpose such as photocopiers, overhead projectors and slide projectors or for scale illumination or indication purposes. Suitable for indoor use and outdoor use without direct sunlight exposure. Please avoid immerse in the water over 30 minutes.

#### Features

- Universal input
- Plastic enclosure IP67
- Overload protection, current limiting, auto recovery
- Protections: short circuit/over load/over voltage
- Protection Class 2
- Fixed output current



#### Technical Specifications



Input Voltage:	180...305V AC (47...63Hz) 254...431V DC
Input Inrush Current, Max.:	40A
Withstand Voltage (I/P-O/P):	3000V AC
Operating Temperature:	-25...+50°C
Weight:	740g

I/P = Input, O/P = Output



Part Nr.	$U_A$ [V]	$I_A$ [mA]	$P_A$ [W]	$DI_A$ [%]	$U_{RN}$ [V <sub>p-p</sub> ]	$h$ [%]
LPC-150-350	215...430	350	150,5	5	2	90
LPC-150-500	150...300	500	150	5	1,5	90
LPC-150-700	107...215	700	150,5	5	1	90
LPC-150-1050	72...144	1050	151,2	5	1	90
LPC-150-1400	54...108	1400	151,2	5	1	90
LPC-150-1750	43...86	1750	150,5	5	1	90
LPC-150-2100	36...72	2100	151,2	5	1	90
LPC-150-2450	31...62	2450	151,9	5	1	90
LPC-150-2800	27...54	2800	151,2	5	1	90
LPC-150-3150	24...48	3150	151,2	5	1	90

$U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $DI_A$  = Output Current Tolerance,  $U_{RN}$  = Ripple & Noise,  $h$  = Typ. Efficiency



#### Note

Devices only for use in equipment with another primary purpose such as photocopiers, overhead projectors and slide projectors or for scale illumination or indication purposes. Suitable for indoor use and outdoor use without direct sunlight exposure. Please avoid immerse in the water over 30 minutes.

## Productinformatie

Artikelnummer	LPC1503150
Merk	MEANWELL

