

VENTILATOR 5V/DC VAPOLAGER 30X30X10MM 8,0M3/H 21DB

€ 7,38

Excl. BTW: € 6,10

Afbeeldingen



Beschrijving

Design



Motor:

Patented One-phase Single Coil

DC Brushless Motor Design

Nr. of Motor Poles:	8
Frame, Impeller:	Filled Thermoplastic PBT (UL94V-O)
Bearing System:	Vapo
	With Magnetic Levitation System
Lead Wire:	AWG28, Stripped, Tinned



Technical Specifications



Rated Voltage	
MC30100_:	5V DC
Operating Voltage	
MC30100_:	2,5...6V DC
	4,5...13,8V DC
Dielectric Strength at 65% r. F.:	
Insulation Resistance at 500V DC:	>500MW
Storage Temperature:	-40...+70°C
Operating Temperature:	-10...+70°C



Part Nr.	U_{Rated}	$P_{Airflow}$	Noise	I	P_{el}	Speed
	[V]	[m ³ /h]	[dBA]	[A]	[W]	[RPM]
MF30100V21000UA99	5	7,98	21	0,08	0,4	9500

P_{Airflow} = Airflow, P_{el} = Rated Power and Current Tolerance, $\pm 15\%$

Productinformatie

Artikelnummer	F0503010VF
Merk	SUNON
Is on Sale	Nee

