

VENTILATOR 5V/DC VAPOLAGER 17X17X8MM 1,1M3/H 14.2DB

€ 11,50

Excl. BTW: € 9,50

## Afbeeldingen



## Beschrijving

### Design



Motor:	Patented One-phase Single Coil
	DC Brushless Motor Design
Nr. of Motor Poles:	8
Frame, Impeller:	Filled Thermoplastic PBT (UL94V-0)

Bearing System:	Vapo
	With Magnetic Levitation System
Lead Wire:	AWG28, Stripped, Tinned



## Technical Specifications



Rated Voltage:	5V DC
Operating Voltage:	2,5...6V DC
Dielectric Strength at 65% r. F.:	500V AC for 1 Min.
Insulation Resistance at 500V DC:	>500MOhm
Storage Temperature:	-40...+70°C
Operating Temperature:	-10...+70°C



Part Nr.	$U_{Rated}$	$P_{Airflow}$	Noise	I	$P_{el}$	Speed
	[V]	[m <sup>3</sup> /h]	[dBA]	[A]	[W]	[RPM]
<b>MC17080V2-A99</b>	5	1,19	16	0,1	0,5	15000

$P_{Airflow}$  = Airflow,  $P_{el}$  = Rated Power and Current Tolerance, ±15%

## Productinformatie

Artikelnummer	F0501708MD
Merk	SUNON
Is on Sale	Nee

