

VENTILATOR 12V/DC VAPOLAGER 25X25X10MM 5,9M3/H 23DB

€ 11,01

Excl. BTW: € 9,10

Afbeeldingen



Beschrijving

Design



Motor:

Patented One-phase Single Coil

DC Brushless Motor Design

Nr. of Motor Poles:	8
Frame, Impeller:	Filled Thermoplastic PBT (UL94V-0)
Bearing System:	Vapo
	With Magnetic Levitation System
Lead Wire:	AWG28, Stripped, Tinned



Technical Specifications



Rated Voltage	
MC25101_:	12V DC
Operating Voltage	
MC25101_:	4,5...13,8V DC
Dielectric Strength at 65% r. F.:	500V AC for 1 Min.
Insulation Resistance at 500V DC:	>500MOhm
Storage Temperature:	-40...+70°C
Operating Temperature:	-10...+70°C



Part Nr.	U_{Rated}	$P_{Airflow}$	Noise	I	P_{el}	Speed
	[V]	[m ³ /h]	[dBA]	[A]	[W]	[RPM]

MF25101V11000UA99	12	6,45	26	0,050	0,6	14000
-------------------	----	------	----	-------	-----	-------

P_{Airflow} = Airflow, P_{el} = Rated Power and Current Tolerance, $\pm 15\%$

Productinformatie

Artikelnummer	F1202510VD
Merk	SUNON
Is on Sale	Nee

