

---

**GESCHAKELDE VOEDING SINGLE OUTPUT 102W 12V/8.5A**

**€ 25,95**

Excl. BTW: € 21,45

**Afbeeldingen**

---



**Beschrijving**

---

**Features**

- Enclosed case, screw terminals
- Universal input
- Overload protection, pulsing hiccup shutdown, auto recovery
- Protections: short circuit/over load/over voltage
- Low profile
- EN60335-1 (PD3), EN61558-1, -2, -16



## Technical Specifications



Input Voltage:	85...264V AC (47...63Hz)
	120...373V DC
Input Inrush Current, Max.:	50A
Leakage Current, Max.:	0,75mA
Output Voltage Adjustment:	±10%
Over Load Protection:	110...150%
Withstand Voltage	
I/P-O/P:	3750V AC
I/P-FG:	2000V AC
O/P-FG:	1250V AC
Operating Temperature:	-30...+70°C
Operating Altitude, Max.:	5000m
Weight:	340g

I/P = Input, O/P = Output, FG = Frame Ground



Part Nr.	U <sub>A</sub>	I <sub>A</sub>	P <sub>A</sub>	DU <sub>A</sub>	U <sub>RN</sub>	h
	[V]	[A]	[W]	[%]	[mV <sub>p-p</sub> ]	[%]
LRS-100-3.3	3,3	0...20	66	3	100	84,5
LRS-100-5	5	0...18	90	2	100	86
LRS-100-12	12	0...8,5	102	1	120	88
LRS-100-15	15	0...7	105	1	120	88,5
LRS-100-24	24	0...4,5	108	1	150	90
LRS-100-36	36	0...2,8	100,8	1	200	90,5

LRS-100-48	48	0...2,3	110,4	1	200	91
------------	----	---------	-------	---	-----	----

$U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise,  $h$  = Efficiency



**Note**

These power supplies are considered as a component that has to be installed in a final equipment.

**Productinformatie**

Artikelnummer	LRS10012
Merk	MEANWELL
Is on Sale	Nee

