

LITHIUM 3.6V 5800MA C 26X50MM

€ 26,04

Excl. BTW: € 21,52

Afbeeldingen



Beschrijving

Technical Specifications



System:	LiSOCl <sub>2</sub>
Nominal Voltage:	3,6V
Cell Construction	
(SAF-)LS_:	Bobbin Construction
LSH_:	Spiral Construction
Operating Temperature Range:	-60...+85°C



Part No.	Cell Size	$C_N$ [mAh]	$I_{max.}$ [mA]	$I_p$ [mA]
SAF-LS14250	1/2AA	1200	35	100
LS14250CNA	1/2AA	1200	35	100
LS14250CNR	1/2AA	1200	35	100
LS142502PF	1/2AA	1200	35	100
LS142503PF	1/2AA	1200	35	100
LS142503PFRP	1/2AA	1200	35	100
LS17330	2/3A	2100	25	120
SAF-LS14500	AA	2600	50	250
LS14500CNA	AA	2600	50	250
LS14500CNR	AA	2600	50	250
LS145002PF	AA	2600	50	250
LS145003PF	AA	2600	50	250
LS145003PFRP	AA	2600	50	250
LS17500	A	3600	100	250
LS17500CNR	A	3600	100	250
LS175002PF	A	3600	100	250
LS175003PF	A	3600	100	250
LSH14	C	5800	1300	2000
LS26500	C	7700	150	300
LSH20	D	13000	1800	4000
LS33600	D	17000	250	400

$C_N$  = Nominal Capacity,  $I_{max.}$  = Continuous Current, max.,  $I_p$  = Pulse Discharge Rate, max.

## Productinformatie

---

Artikelnummer	LSH14
Merk	SAFT

