

LITHIUM 3.6V 1200MA 1/2AA 14.1X25MM

€ 7,57

Excl. BTW: € 6,26

## Afbeeldingen



## Beschrijving

### Features

- Extremely low self-discharge (1% or less per year)
- High energy density
- Suited for long-term use with low current
- For operation at low current levels with long stands
- Intermittent discharge with medium current level provided the average is not below
- Wide temperature range from -55°C to +85°C
- Excellent shelf life (10 years)
- SL-\_/S: Standard version
- SL-\_/T: Solder lugs
- SL-\_/P: Axial connection



### Technical Specifications



System:

LiSOCl<sub>2</sub>

Nominal Voltage:	3,6V
Temperature Range:	-55...+85°C

Part No.	Cell Size	$C_N$ [mAh]	$I_N$ [mA]	$I_{max}$ [mA]
SL-350/S	1/2AA	1200	0,6	6
SL-350/T	1/2AA	1200	0,6	6
SL-350/P	1/2AA	1200	0,6	6
SL-351/S	2/3AA	1600	1	10
SL-351/T	2/3AA	1600	1	10
SL-360/S	AA	2400	2	20
SL-360/T	AA	2400	2	20
SL-360/P	AA	2400	2	20

$C_N$  = Nominal Capacity,  $I_N$  = Nominal Current,  $I_{max}$  = Continuous Discharge Current, max.

## Productinformatie

Artikelnummer	SL350/S
Merk	TADIRAN

