

## TRANSFORMATOR 0.35VA 1X15V 1X23MA

€ 4,38

Excl. BTW: € 3,62

### Afbeeldingen



### Beschrijving

#### Features

- Winding of double coated copper wire for better insulation, vacuum casted, two chambers
- Connections for PCB use



#### Technical Specifications



|   |         |
|---|---------|
| Temperature Class <sup>1)</sup> :                             | Ta 70/B |
| End Temperature in Case of Short Circuit, Max <sup>2)</sup> : | 175°C   |
| End Temperature in Standard Use:                              | 120°C   |
| Permissible Overtemperature <sup>3)</sup> :                   | 50K     |

|  |                         |
|--|-------------------------|
| Primary Voltage (50/60Hz):               | 230V AC                 |
| Power, Max. (Ta 70/B) <sup>2)</sup> :    | 0,35VA                  |
| Insulation Voltage:                      | 4kV/50Hz                |
| No-Load Voltage (According to VDE 0570): | <2 x U <sub>N sec</sub> |

<sup>1)</sup> The Maximum Permissible Continuous Ambient Temperature Applies in the Event of Short-Circuit, <sup>2)</sup> Taking into Account the Indicated Temperature Resistance Class, <sup>3)</sup> At 70°C Ambient Temperature

## Productinformatie

|               |          |
|---------------|----------|
| Artikelnummer | 1150003M |
| Merk          | HAHN     |
| Is on Sale    | Nee      |

