
ADAPTER 15V 800MA GESCHAKELD

€ 19,95

Excl. BTW: € 16,49

Afbeeldingen



Beschrijving

Features

- Plug-in switching power supply with europlug
- Universal input
- Overload protection, pulsing hiccup shutdown, auto recovery
- Protections: short circuit/over load/over voltage
- Insulation Class II
- Low no load power consumption
- Energy efficiency level VI



Technical Specifications



Input Voltage:	90...264V AC (47...63Hz)
Input Inrush Current, Max.:	60A
No Load Power Consumption, Max.:	0,075W
Operating Temperature:	-20...+60°C
Cable Length	
15V	1,8m
Input Plug:	Euro
Output Plug, Coax:	2,1x5,5mm
Average active efficiency:	>82,96%
Efficiency at low load, typ. (10%):	>75%
Weight:	100g



Part Nr.	U_A	I_A	P_A	DU_A	U_{RN}	h
	[V]	[A]	[W]	[%]	[mV _{p-p}]	[%]
PSS1508A	15	0...0,8	12	3	80	84,5

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Productinformatie

Artikelnummer	PSS1508A
Merk	MEANWELL

