

## LED DRIVER 16-32VDC 250MA 8W

€ 7,95

Excl. BTW: € 6,57

### Afbeeldingen



### Beschrijving

#### Features

- Universal input
- Plastic enclosure IP42
- Protections: short circuit
- Suitable for LED lighting and moving sign applications
- Constant current



#### Technical Specifications



Input Voltage:

180...264V AC (47...63Hz)

254...370V DC

Input Inrush Current, Max.:	70A
Withstand Voltage (I/P-O/P):	3750V AC
Operating Temperature:	-30...+70°C
Weight:	50g

I/P = Input, O/P = Output



Part Nr.	$U_A$	$I_A$	$P_A$	$U_{RN}$	$h$
	[V]	[mA]	[W]	[mV <sub>p-p</sub> ]	[%]
APC8E250	16...32	250	8	350	81,5
APC8E350	11...23	350	8,05	300	80,5
APC8E500	8...16	500	8	300	79
APC8E700	6...11	700	7,7	250	77,5

$U_A$  = Output Voltage Range,  $I_A$  = Output Current,  $P_A$  = Output Power,  $U_{RN}$  = Ripple & Noise,  $h$  = Typ. Efficiency



#### Note

These power supplies are considered as a component that has to be installed in a final equipment.

## Productinformatie

Artikelnummer	APC8E250
Merk	MEANWELL

