

LED VOEDING 48V/3.2A 151W IP67 BEHUIZING

€ 49,95

Excl. BTW: € 41,28

Afbeeldingen



Beschrijving

Features

- Plastic enclosure IP67
- Overload protection, pulsing hiccup shutdown, auto recovery
- Protections: short circuit/over load/over voltage
- Fixed output voltage



Technical Specifications



Input Voltage:	180...305V AC (47...63Hz)
	254...431V DC
Input Inrush Current, Max.:	60A
Over Load Protection:	110...150%
Withstand Voltage (I/P-O/P):	3000V AC
Operating Temperature:	-25...+65°C
Weight:	740g

I/P = Input, O/P = Output



Part Nr.	U_A	I_A	P_A	DU_A	U_{RN}	h
	[V]	[A]	[W]	[%]	[mV _{p-p}]	[%]
LPV15012	12	0...10	120	5	200	87
LPV15015	15	0...8	120	5	200	88
LPV15024	24	0...6,3	151,2	5	200	89
LPV15036	36	0...4,2	151,2	5	200	89
LPV15048	48	0...3,2	153,6	5	200	90

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Typ. Efficiency



Note

Devices only for use in equipment with another primary purpose such as photocopiers, overhead projectors and slide projectors or for scale illumination or indication purposes.

Suitable for indoor use and outdoor use without direct sunlight exposure. Please avoid immerse in the water over 30 minutes

Productinformatie

Artikelnummer	LPV15048
Merk	MEANWELL

