


LED DRIVER 2-41.5VDC 350MA 14W 115X34X19MM

€ 19,95

Excl. BTW: € 16,49

Afbeeldingen



FEATURES	
Rated Voltage	100 V 110...227 V 220...240 V
Constant Current ▾	
Dimming:	NOT DIMMABLE
Additional technical features:	RIPPLE FREE ACTIVE PFC (pF<0.9) SELV < 5 WIDE RANGE INPUT VOLTAGE
Approvals:	ENEC EAC CE
Plastic case:	IP 20 (Independent Use)
Minimum cut-out hole diameter:	40 mm
Size:	115 x 19 x 34 mm
last update:	7/30/2021
Output voltage (min/max) ^	
350 mA	2...41,5

Model	Output	Power	Temp	Temp	Temp	Temp	Temp	Temp	Temp
LED 115 34x19mm 350mA	2...41,5	14W	25°C	55°C	75°C	85°C	95°C	105°C	115°C
LED 115 34x19mm 350mA	2...41,5	14W	25°C	55°C	75°C	85°C	95°C	105°C	115°C
LED 115 34x19mm 350mA	2...41,5	14W	25°C	55°C	75°C	85°C	95°C	105°C	115°C

Beschrijving

Features

- Active Power Factor Corrector.
- IP20 independent driver, for indoor use.
- Class II protection against electric shock for direct or indirect contact.
- Supplied with terminal cover and cable retainer.
- Input and output terminal blocks on opposite sides (wire cross-section up to 2,5 mm² / AWG13).
- Single terminal block on primary and secondary circuit.
- Clamping screws on primary and secondary circuits for cables with diameter: min. 3 mm - max. 8 mm.
- Driver can be secured with slot for screws.
- Protections:
 - against overheating and short circuits;
 - against mains voltage spikes;

- against overloads.
- Thermal protection = C.5.a.

[Klik hier om datasheet te bekijken](#)

Productinformatie

Artikelnummer	127713
Merk	TCI
Is on Sale	Nee

