


## LED DRIVER 2-59VDC 350MA 20W

€ 25,95

Excl. BTW: € 21,45

### Afbeeldingen



### Beschrijving

#### Features

- Universal input
- Constant current
- Not dimmable
- Plastic housing IP20
- Low profile (13mm high)
- Overload protection by shutdown, auto recovery
- Protected against short circuit, overload
- For LED and lighting applications
- Safety standards: IEC 61347-1; IEC 61347-2-13; EN 61347-1; EN 61347-2-13
- EMC standards: EN 55015
- 3 years manufacturer warranty



#### Technical Specifications



Input Voltage:	198...264V AC (47...63Hz)
Input Inrush Current, Max.:	8A
No-load power, less than:	0,5W
Withstand Voltage (I/P-O/P):	3750V AC
Operating Temperature:	-20...+45°C
Dimensions(LxWxH):	128x50x13mm
Weight:	75g

I/P = Input, O/P = Output



Part Nr.	$U_A$	$I_A$	$P_A$	$I_{RN}$	h
	[V]	[mA]	[W]	[A <sub>p-p</sub> ]	[%]
RACD20-350-LP	2...59	350	21	0,05	86
RACD20-500-LP	2...40	500	20	0,05	85
RACD20-700-LP	2...31	700	22	0,05	85

$U_A$  = Output Voltage,  $I_A$  = Output Current,  $P_A$  = Output Power,  $I_{RN}$  = Ripple & Noise, h = Typ. Efficiency

## Productinformatie

Artikelnummer	RACD20-35L
Merk	RECOM

