


LED DRIVER 2-19VDC 700mA 12W

€ 22,95

Excl. BTW: € 18,97

Afbeeldingen



Beschrijving

Features

- Universal input
- Constant current
- Not dimmable
- Plastic housing IP20
- Low profile (13mm high)
- Overload protection by shutdown, auto recovery
- Protected against short circuit, overload
- For LED and lighting applications
- Safety standards: IEC 61347-; IEC 61347-2-13; EN 61347-; EN 61347-2-13
- EMC standards: EN 55015
- 3 years manufacturer warranty



Technical Specifications



Input Voltage:	198...264V AC (47...63Hz)
Input Inrush Current, Max.:	8A
No-load power, less than:	0,5W
Withstand Voltage (I/P-O/P):	3750V AC
Operating Temperature:	-20...+50°C
Dimensions(LxWxH):	128x50x13mm
Weight:	70g

I/P = Input, O/P = Output



Part Nr.	U_A	I_A	P_A	I_{RN}	h
	[V]	[mA]	[W]	[A _{p-p}]	[%]
RACD12-350-LP	2...37	350	13	0,05	86
RACD12-500-LP	2...24	500	12	0,05	81
RACD12-700-LP	2...19	700	13	0,05	85

U_A = Output Voltage, I_A = Output Current, P_A = Output Power, I_{RN} = Ripple & Noise, h = Typ. Efficiency



Note

Power supply for the operation of LED light sources.

Used electronic devices are recyclable materials and do not belong in household waste.

If the device is at the end of its service life, dispose of it in accordance with the applicable legal regulations at the collection points of the disposal system. Disposal via the household waste is prohibited

Productinformatie

Artikelnummer	RACD12-70L
Merk	RECOM

