


## GESCHAKELDE VOEDING SINGLE OUTPUT 750W 12V/62.5A

€ 259,00

Excl. BTW: € 214,05

### Afbeeldingen



### Beschrijving

#### Features

- Enclosed case, built-in fan, screw terminals
- Universal input
- Overload protection, current limiting, auto recovery
- Protections: short circuit/over load/over voltage
- Built-in active PFC function
- Low profile
- Built-in remote On/Off control
- Built-in remote sense function
- DC OK signal
- Built-in auxiliary power 5V/0,5A
- Trimming function for output voltage and output current between 40...110% by 2...5,5VDC external voltage



#### Technical Specifications



Input Voltage:	90...264V AC (47...63Hz)
	127...370V DC
Input Inrush Current, Max.:	40A
Leakage Current, Max.:	2mA
Output Voltage Adjustment:	±10%
Over Load Protection:	105...125%
Withstand Voltage	
I/P-O/P:	3000V AC
I/P-FG:	2000V AC
O/P-FG:	500V AC
Operating Temperature:	-30...+70°C
Weight:	1640g

I/P = Input, O/P = Output, FG = Frame Ground



Part Nr.	$U_A$	$I_A$	$P_A$	$DU_A$	$U_{RN}$	$h$
	[V]	[A]	[W]	[%]	[mV <sub>p-p</sub> ]	[%]
RSP-750-5	5	0...100	500	2	150	82
RSP-750-12	12	0...62,5	750	1	150	87
RSP-750-15	15	0...50	750	1	150	89
RSP-750-24	24	0...31,3	751,2	1	150	90,5
RSP-750-27	27	0...27,8	750,6	1	150	90,5
RSP-750-48	48	0...15,7	753,6	1	150	92

$U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $U_{adj}$  = Output Voltage Adjustment,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise,  $h$  = Efficiency

## Productinformatie

---

Artikelnummer	RSP75012
Merk	MEANWELL

