


GESCHAKELDE VOEDING SINGLE OUTPUT 751W 24V/31.3A

€ 259,00

Excl. BTW: € 214,05

Afbeeldingen



Beschrijving

Features

- Enclosed case, built-in fan, screw terminals
- Universal input
- Overload protection, current limiting, auto recovery
- Protections: short circuit/over load/over voltage
- Built-in active PFC function
- Low profile
- Built-in remote On/Off control
- Built-in remote sense function
- DC OK signal
- Built-in auxiliary power 5V/0,5A
- Trimming function for output voltage and output current between 40...110% by 2...5,5VDC external voltage



Technical Specifications



Input Voltage:	90...264V AC (47...63Hz)
	127...370V DC
Input Inrush Current, Max.:	40A
Leakage Current, Max.:	2mA
Output Voltage Adjustment:	±10%
Over Load Protection:	105...125%
Withstand Voltage	
I/P-O/P:	3000V AC
I/P-FG:	2000V AC
O/P-FG:	500V AC
Operating Temperature:	-30...+70°C
Weight:	1640g

I/P = Input, O/P = Output, FG = Frame Ground



Part Nr.	U_A	I_A	P_A	DU_A	U_{RN}	h
	[V]	[A]	[W]	[%]	[mV _{p-p}]	[%]
RSP-750-5	5	0...100	500	2	150	82
RSP-750-12	12	0...62,5	750	1	150	87
RSP-750-15	15	0...50	750	1	150	89
RSP-750-24	24	0...31,3	751,2	1	150	90,5
RSP-750-27	27	0...27,8	750,6	1	150	90,5
RSP-750-48	48	0...15,7	753,6	1	150	92

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, U_{adj} = Output Voltage Adjustment, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Productinformatie

Artikelnummer	RSP75024
Merk	MEANWELL

