

PULSE TRAF0 17MH 2:1:1

€ 7,95

Excl. BTW: € 6,57

Afbeeldingen



Beschrijving

Features

- Single and double secondary winding
- Vacuum potting
- Allows high potential difference voltage scaling
- Very low partial discharge effects
- PCB through-hole mounting



Technical Specifications



Max. Operating Frequency: 40kHz

Temperature Range: -25...+70°C



| Part Nr. | Transformation | I_{ign} [A] | L [mH] | R_{prim} [Ohm] | R_{sek} [Ohm] |
|----------|----------------|------------------|-----------|---------------------|--------------------|
| IT213 | 1:1:1 | 0,25 | 6,5 | 1,4 | 1,4 |
| IT233 | 1:1:1 | 0,25 | 3 | 0,8 | 0,8 |
| IT239 | 1:1 | 0,25 | 3 | 0,9 | 0,9 |
| IT242 | 1:1:1 | 0,1 | 2,5 | 0,75 | 0,75 |
| IT243 | 1:1:1 | 0,1 | 2,5 | 0,8 | 0,8 |
| IT244 | 3:1:1 | 0,1 | 15 | 2,8 | 0,9 |
| IT245 | 1:1 | 0,1 | 8 | 1,48 | 1,48 |
| IT246 | 2:1 | 0,1 | 7 | 2,1 | 1,1 |
| IT248 | 2:1 | 0,25 | 17 | 3,2 | 1,6 |
| IT249 | 2:1:1 | 0,25 | 17 | 3,1 | 1,5 |
| IT253 | 1:1:1 | 0,25 | 1,1 | 0,55 | 0,55 |
| IT255 | 1:1 | 0,25 | 2,2 | 0,8 | 0,8 |
| IT258 | 1:1 | 1 | 2,5 | 0,62 | 0,75 |
| IT260 | 3:1 | 0,1 | 12 | 2 | 0,8 |
| IT313 | 1:1:1 | 1 | 3 | 0,33 | 0,4 |
| IT314 | 3:1:1 | 1 | 35 | 1,6 | 0,7 |

I_{ign} = Ignition Current @ 40°C, L = Inductance, R_{prim} = Primary DC Resistance, R_{sec} = Secondary DC Resistance

Productinformatie

| | |
|---------------|-----------|
| Artikelnummer | IT249 |
| Merk | SCHAFFNER |

